



WARRIOR® SS-10

SHOWER SEAL

LEAKAGE PREVENTION, PROTECT AND EXTEND DURABILITY OF WATERPROOFING SYTEM, STOP LEAKING TOILETS WITHOUT REMOVING THE TILES.



USES

- To prevent water leakage
- To provide protection to the existing waterproofing system and to extend its durability
- To stop water leakage without needing to remove the existing tiles
- To reduce water absorption of both interior and exterior wall, tiles, stone, granite, marbles and cement surfaces.

FEATURES

- **SS10** is a ready-to-use aqueous silicone ester emulsion.
- **SS10** provides long lasting sub-surface protection and does not change the surface appearance.
- **SS10** does not form film on surface, thus eliminating the wearing off issue over times.
- **SS10** has high surface colour stability, leaving minimal surface appearance changes.
- **SS10** is easy to use: simply by spray or brush.

APPLICATION METHODS

TOILET

1. Ensure surface to be treated is clean and intact. It should be free from bitumen, oil, grease and loose particles. All the cracked and defective tile joints must be removed.
2. Allow the toilet to dry for 1 day before application.
3. Apply **SS10** generously by brush or by spray, onto the entire wall and floor tile joints, edges of toilet bowls and nailing point of shower screen.
4. After one hour, apply second coat of **SS10**.



WARRIOR® SS-10

SHOWER SEAL

LEAKAGE PREVENTION, PROTECT AND EXTEND DURABILITY OF WATERPROOFING SYSTEM, STOP LEAKING TOILETS WITHOUT REMOVING THE TILES.

5. After one hour, patch back the defects on tile joints (if necessary, using tile grout added with **W1 Cement Strengthener**).
6. Allow one day for the treatment to dry and cure.
7. Job done.

Remark:

- **SS10** is to be absorbed into the substrate. Do not apply **SS10** on non-absorbent surfaces, such as glass, aluminium, etc.
- Wipe away excessive **SS10** on surface after 30 minutes of application. Do not allow thick patch of **SS10** to air dry on the surface as it may cause unwanted surface stain.
- Always conduct a patch test, by applying **SS10** on a remote corner of the toilet. After 24 hours, check for any unwanted surface appearance changes. Carry out full application only when no surface change is visible.

Physical Form White liquid with slight alcoholic odour.

Coverage Approx 30 sq. ft /kg depending upon the porosity of the Substrate

PACKING

500 ml-bottle / 1 L-bottle