



WARRIOR® W-88

MULTI PURPOSE ACRYLIC GEL

SEALING, BONDING, PRIMING, WATERPROOFING

FEATURES

- **W88** is a high concentration acrylic gel, suitable for multi-purpose applications, both indoor and outdoor.
- High viscosity for sealing cracks and holes permanently.
- High bonding strength on various surfaces.
- Excellent anti-blistering performance, making it a high-performance paint and waterproofing primer.
- Water resistant.



APPLICATION METHODS

Wallpaper Glue (For gluing of new wallpaper/ repair of debonded wallpaper):

1. Clean the wall surface.
2. Brush or roll **W88** on the back of wallpaper and on the wall.
3. Smoothen the wallpaper from the center outward, using a broad plastic scraper or squeegee. Push out any air pockets towards the edges of wallpaper.
4. Smoothing process should be done within 10 minutes.
5. Wash all residue with a clean damp sponge.

Remarks:

*Complete drying of **W88** could take around 2 ~ 3 days. Do not tamper with the wallpaper before it has dried thoroughly.*

Coverage: +/- 5m² per kg



Powdery Surface Treatment:

- Dilute **W88** with 50% of water (by weight) and spray/brush onto the surface.
- **W88** will lock the powdery particles and dry to form a smooth surface.

Priming (for painting, waterproofing, tiling, cement patching):

1. Clean and surface to be bonded, remove all loose particles.
2. Dilute **W88** with 20% of water. Brush/ roll onto the surface to be bonded.
3. Allow the coating to dry for 24 hours.
4. Apply subsequent coatings (paint, waterproofing or tile bonding cement).



WARRIOR® W-88

MULTI PURPOSE ACRYLIC GEL

SEALING, BONDING, PRIMING, WATERPROOFING

Remarks:

Protect the coating surface from any dirt, throughout the drying process.

Coverage: 6~8m² per kg

Crack filling and joint sealing:

Eg: window frame, kitchen sink edge, shower screen joint, bathroom drain cover, around air cond pipe, etc.

- Brush **W88** directly over the edge/ joint to be protected.
- For crack/ hole filling, press W88 into the holes using scrapper.

Remarks:

*Fully cured **W88** is water resistant and can be painted over.*

TECHNICAL DATA

Colour: White, viscous liquid

pH: 7.5 ~ 9

Shelf Life: 12 months

PACKING

0.5 kg-can/ 4 kg-pail/ 20 kg-pail